

**СЕРИЯ T-MI|
T-MIO|T-MI.3W
100...101**

The image shows two schematic diagrams of T-MI valves. The left diagram is labeled 'T-MI.3W (H3)' and shows a valve with three ports: port 1 at the bottom, port 2 at the top, and port 3 on the right. The right diagram is labeled 'T-MI | T-MIO (H3)' and shows a valve with two ports: port 1 at the bottom and port 2 at the top. Both diagrams include a symbol for a solenoid coil on the right side of the valve body.



T-MI | T-MIO (H3)

T-MI.3W (H3)

G	A	B	C	D	E	F	H	I
1/8	35	56	22	29,4	66,7	18,9	19,9	72,5
1/4	35	56	22	29,4	66,7	18,9	19,9	72,5

G	A	B	C	D	E	F	H
1/8	35	56	22	29,4	66,7	18,9	19,9
1/4	35	56	22	29,4	66,7	18,9	19,9

Полезная информация: 1 бар:14,5 PSI:10 м Н₂O:10 Н/см²:1 кг/см²:10⁵Па; 1 PSI:69 мбар; 1 м³/ч:4,405 галлон/мин:16,7 л/мин.; 1 галлон/мин.:0,227 м³/ч; Cv:1,16 Kv; 0 °C:89,6 F
Уплотнения: FPM (VITON) - фторэластомер.